

# CORDLESS IMPULSE WRENCH WITH SHUT OFF

POWERFUL, VERY ACCURATE AND NO KICK-BACK



Yokota YZ-T cordless impulse wrenches with shut-off are powerful, very accurate and most important, have no kick-back. The very compact design offers great accessibility to the joint. Tightening bolts with torque levels up to 80 Nm with very high speed and remarkably low reaction forces. Adjusting the tool settings for the specific bolted joint is done by Programming Console PC-2-F and cable CC-1. Auditory and visual feedback on the result of the screwing process.

## CHARACTERISTICS

- With built-in retention in the square drive
- No kickback
- High speed fastening
- Hybrid technology
- DC-drive brushless motor

## ACCESSORIES

Delivery is inclusive battery and exclusive charger.



Li-Ion battery



Charger



Programming console



Cable

Type	Order Number
<b>Li-Ion battery (0,41 kg) 18V 2 Ah</b>	BPL-1820
<b>Charger 18 Volt (40 min.)</b>	BC2075MX
<b>Programming console</b>	PC-2-F
<b>Cable (2 mtr)</b>	CC-1

Type	Square Drive / Hexagon	Bolt capacity mm	Speed 1 RPM <sup>(1)</sup>	Speed 2 RPM <sup>(2)</sup>	Speed 3 RPM <sup>(3)</sup>	Torque Nm	Weight with battery	Length mm	Distance to the spindle center mm	Vibration m/s <sup>2</sup>	Noise level dB(A)
<b>YZ-T600A</b>	1/4" Hex	6	1.200-1.500	1.500-3.000	1.500-4.800	5-18	1,4	161	29,5	<2,5	67
<b>YZ-T600E</b>	3/8" Sq.	6	1.200-1.500	1.500-3.000	1.500-4.800	7-20	1,4	161	29,5	<2,5	67
<b>YZ-T800A</b>	1/4" Hex	6-8	1.200-1.500	1.500-3.000	2.000-4.800	10-30	1,5	166	29,5	<2,5	68
<b>YZ-T800E</b>	3/8" Sq.	6-8	1.200-1.500	1.500-3.000	2.000-4.800	15-35	1,5	166	29,5	<2,5	68
<b>YZ-T900E</b>	3/8" Sq.	8-10	1.200-1.500	1.500-3.000	2.000-4.800	30-50	1,6	173	29,5	<2,5	69
<b>YZ-T950E</b>	3/8" Sq.	8-10	1.200-1.500	1.500-3.000	2.000-4.800	40-60	1,65	173	29,5	<2,5	70
<b>YZ-T980E</b>	3/8" Sq.	10	1.200-1.500	1.500-3.000	2.000-3.000	45-65	2,2	241	34	<2,5	70
<b>YZ-T1000E</b>	1/2" Sq.	10-12	1.200-1.500	1.500-3.000	2.000-3.000	60-80	2,2	241	34	<2,5	70

<sup>1)</sup> From the first stage of the trigger | <sup>2)</sup> From the second stage of the trigger | <sup>3)</sup> From shifting level