

CORDLESS IMPULSE WRENCH NON SHUT OFF

POWERFUL, VERY ACCURATE AND NO KICK-BACK



The compact design of the YZ-NP range offers great accessibility to the joint. Tightening bolts M6 up to M10 with torque levels up to 65 Nm with very high speeds and remarkably low reaction forces. The Output Adjustment Dial offers 4 settings of motor output by the dial (2000, 3000, 4000, 4800 rpm) and the combination of adjustment of the relief valve and speed setting of the motor gives a great fit-forpurpose adaptation to the specific bolted joint. The YOKOTA non-shut off cordless impulse wrench is the perfect solution for applications where cables or hoses are disruptive. Pulse check function: By teaching the tool the impulse cycle as a reference point, the tool is able to give a warning message for upcoming maintenance needs.

CHARACTERISTICS


- Complete freedom of movement by use of batteries
- High speed fastening
- No Kickback
- Ergonomic design
- Electric (brushless) DC-drive
- Adjustable RPM
- Error LED indication for Overheat & Motor/driver errors and battery capacity warning



Battery 18V 2 AH (BPL-1820)



Charger (BC2075MX)



Have	tο	he	ordered	seperately	
Have	ιO	ne	ordered	Seperatery	

Туре	Volt. V	Accu type	Square drive	Bolt capacity mm	RPM	Torque Nm	Weig without battery	ht kg with battery	Vibration m/s ²	Noise level dB(A)	Dimer A mm	nsions B mm
YZ-NP600A-Z	18 V	Li-ion 2 AH	1/4" 6K	6	2000-4.800	7 - 18	1	1,41	<2,5	72	152	29,5
YZ-NP600E-Z	18 V	Li-ion 2 AH	3/8" 4K	6	2000-4.800	9-20	1	1,41	<2,5	72	152	29,5
YZ-NP800A-Z	18 V	Li-ion 2 AH	1/4" 6K	6-8	2000-4.800	15-30	1,05	1,46	<2,5	75	157	29,5
YZ-NP800E-Z	18 V	Li-ion 2 AH	3/8" 4K	6-8	2000-4.800	18-35	1,05	1,46	<2,5	75	157	29,5
YZ-NP900E-Z	18 V	Li-ion 2 AH	3/8" 4K	8 - 10	2000-4.800	34-50	1,20	1,61	<2,5	77	164	29,5
YZ-NP950E-Z	18 V	Li-ion 2 AH	3/8" 4K	8 - 10	2000-4.800	45-60	1,25	1,66	<2,5	78	164	29,5